# **HIGH DEFINITION Monitor**



ConMed Linvatec is proud to offer the VP4726/F High Definition Monitor. This 26 inch 1080p medical grade monitor incorporates a 16:9 aspect ratio and TrueHD picture quality. Available with or without fiber optic input. You can now maximize the benefits of High Definition technology at the cutting edge of surgical HDTV.

- Fully HD and Digital Compatible
- Unrivalled 1920 x 1200 Resolution
- Sealed Front Panel in Light-weight Design with VESA Mount
- Wide-screen 16:9 aspect ratio
- PIP functionality





**HD** 1080p







The VP4726/F enable the wide-screen viewing of High Definition images using HD-SDI, DVI, or Fiber Optic (VP4726F only) video inputs.





Catalog Number

VP4726 VP4726F **Description** HD LCD Monitor

HD LCD Monitor, with Fiber Optic Input

**VP4726/F Specifications:** 

LCD Panel: Type TFT Active Matrix LCD with an AR-coated protection panel

Resolution (W x H) 1920 x 1200 (WUXGA)

Picture Size (W x H) Approximately 21.7 x 13.6 inches (551 x 345mm)

Picture Size (Diagonal) 26 inches (660mm)

**HIGH DEFINITION Monitor** 

 Aspect Ratio
 16:9

 Contrast Ratio
 1000:1

 Luminance
 400 cd/m²

Viewing Angle 89° /89° /89° /89°

Dimensions (W x H x D)

 $\begin{array}{ccc} & & & & 24.5 \times 16.6 \times 4.0 \\ & & & \\ & & mm & & 622 \times 422 \times 102 \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ &$ 

# Input/Output

Inputs

 SDI, HD-SDI
 BNC (x1)

 S-video, Y/C
 BNC (x2)

 R/G/B/S, YPbPr
 BNC (x5)

 Composite
 BNC (x1)

 DVI
 DVI-d

 VGA
 HD-15

Fiber Optic 4 pin (VP4726F only)

Control Inputs

**GPIO** 

Serial Remote D-sub 9pin, RS-232C

RJH-4

Outputs

SDI, HD-SDI BNC (x1) DVI DVId

## **General**

Power Consumption

Maximum 120W Stand-by Mode 20W

Power Requirement

 Display
 24 VDC, 6.25A Max

 DC Power Supply
 100 to 240 VAC, 50/60Hz

Temperature

Operating 0 to +40° C (+32 to +104° F) Storage -20 to +60° C (-4 to 140° F)

Humidity

Operating 30 to 75% non-condensing Storage 10 to 85% non-condensing

Mounting 100mm VESA

## CONMED CORPORATION PRODUCT AREAS:

ARTHROSCOPY • ELECTROSURGERY • ENDOSCOPY • ENDOSURGERY • GASTROENTEROLOGY • INTEGRATED SYSTEMS • PATIENT CARE • POWERED INSTRUMENTS • PULMONOLOGY



11311 Concept Boulevard Largo, FL 33773-4908 (727) 392-6464

Customer Service: 1-800-237-0169

FAX: (727) 399-5256

International FAX: +1 (727) 397-4540 email: customer\_service@linvatec.com

www.linvatec.com